



**CR15wiNG**

**Future-ready Security with Wi-Fi Access Point for SOHO/ROBO networks**

Data Sheet 

CR15wiNG is the Next-Generation Unified Threat Management appliance with Wi-Fi access points that offer “the fastest UTM’s made for SMBs” to small offices with high performance security over WLAN. CR15wiNG appliances come with 3x3 MIMO technology that greatly enhances wireless range and performance. It supports 802.11n/b/g wireless standards. Combined with security over wired networks offered by its range of UTM appliances, Cyberoam enables organizations to overcome the physical limitations of securely accessing network resources and offers more user flexibility, user productivity and lower network ownership costs.


The best-in-class hardware along with software to match, enables the NG series to offer unmatched throughput speeds, compared to any other UTM appliance in this market segment. This assures support for future IT trends in organizations like high-speed Internet and rising number of devices in organizations – offering future-ready security for small office networks.



Cyberoam’s Layer 8 technology that treats user-identity as the 8th Layer or the HUMAN layer in the protocol stack, works even in WLAN environments, to allow Identity-based security policies in dynamic IP environment.

**The ‘Next-Generation’ UTM Series for SOHO:**

Faster performance, broader coverage with 3x3 MIMO Technology

Cyberoam’s **Layer 8 Technology** treats “User Identity” as the 8th Layer in the protocol stack



L8	<b>USER</b>	
L7	<b>Application</b>	
L6	<b>Presentation</b>	ASCII, EBCDIC, ICA
L5	<b>Session</b>	L2TP, PPTP
L4	<b>Transport</b>	TCP, UDP
L3	<b>Network</b>	192.168.1.1
L2	<b>Data Link</b>	00-17-BB-8C-E3-E7
L1	<b>Physical</b>	

Cyberoam UTM offers security across Layer 2-Layer 8 using Identity-based policies

**Cyberoam UTM features assure Security, Connectivity, Productivity**

**Security**

**Network Security**

- Firewall
- Intrusion Prevention System
- Wireless Security

**Content Security**

- Anti-Virus/Anti-Spyware
- Anti-Spam (Inbound/Outbound)<sup>###</sup>
- HTTPS/SSL Content Security

**Administrative Security**

- Next-Gen UI
- iView- Logging & Reporting



**Connectivity**

**Business Continuity**

- Multiple Link Management

**Network Availability**

- VPN
- 3G/4G/WiMAX Connectivity

**Future-ready Connectivity**

- “IPv6 Ready” Gold Logo



**Productivity**

**Employee Productivity**

- Content Filtering
- Instant Messaging Archiving & Controls

**IT Resource Optimization**

- Bandwidth Management
- Traffic Discovery
- Application Visibility & Control

**Administrator Productivity**

- Next-Gen UI



<b>Interfaces</b>	
Copper GbE Ports	3
Configurable	
Internal/DMZ/WAN Ports	Yes
Console Ports (RJ45/DB9)	1
USB Ports	2
<b>Built-in Wireless LAN</b>	
Wireless Standards	IEEE 802.11 a/b/g/n (WEP, WPA, WPA2, 802.11i, TKIP, AES, PSK)
<b>Antenna</b>	
Antenna	Detachable 3x3 MIMO
<b>Access Points</b>	
Access Points	Up to 8 ssid
<b>Transmit Power (EIRP)</b>	
Transmit Power (EIRP)	11n HT40 : +15dBm 11b CCK: +15dBm 11g OFDM: +15dBm
<b>Receiver Sensitivity</b>	
Receiver Sensitivity	-68dBm at 300Mbps -70dBm at 54Mbps -88dBm at 6Mbps
<b>Frequency Range</b>	
Frequency Range	2.412 GHz - 2.472 GHz 5.200 GHz - 5.825 GHz

<b>Number of Selectable Channels</b>	
Number of Selectable Channels	USA (FCC) - 11 channels, EU (ETSI) / Japan (TELEC) - 13 channels

<b>Data Rate</b>	
Data Rate	802.11n: up to 450Mbps, 802.11b: 1, 2, 5, 5, 11Mbps, 802.11g: 6, 9, 12, 18, 24, 36, 48, 54Mbps

<b>System Performance*</b>	
Firewall Throughput (UDP)	1,000 (Mbps)
Firewall Throughput (TCP)	750 (Mbps)
New sessions/second	3,500
Concurrent sessions	60,000
IPSec VPN Throughput	110 (Mbps)
No. of IPSec Tunnels	50
SSL VPN Throughput	50 (Mbps)
Anti-Virus Throughput	180 (Mbps)
IPS Throughput	140 (Mbps)
UTM Throughput	80 (Mbps)

- Stateful Inspection Firewall**
- Layer 8 (User - Identity) Firewall
  - Multiple Security Zones
  - Access Control Criteria (ACC) - User - Identity, Source & Destination Zone, MAC and IP address, Service
  - UTM policies - IPS, Web Filtering, Application Filtering, Anti-Virus, Anti-Spam and Bandwidth Management
  - Layer 7 (Application) Control & Visibility
  - Access Scheduling
  - Policy based Source & Destination NAT
  - H.323, SIP NAT Traversal
  - 802.1q VLAN Support
  - DoS & DDoS Attack prevention
  - MAC & IP-MAC filtering and Spoof prevention

- Gateway Anti-Virus & Anti-Spyware**
- Virus, Worm, Trojan Detection & Removal
  - Spyware, Malware, Phishing protection
  - Automatic virus signature database update
  - Scans HTTP, HTTPS, FTP, SMTP, POP3, IMAP, IM, VPN Tunnels
  - Customize individual user scanning
  - Scan and deliver by file size
  - Block by file types
  - Add disclaimer/signature

- Gateway Anti-Spam**
- Inbound Scanning
  - Real-time Blacklist (RBL), MIME header check
  - Filter based on message header, size, sender, recipient
  - Subject line tagging
  - IP address Black list/White list
  - Redirect Spam mails to dedicated email address
  - Image-based Spam filtering using RPD Technology
  - Zero hour Virus Outbreak Protection
  - IP Reputation-based Spam filtering

- Intrusion Prevention System**
- Signatures: Default (4500+), Custom
  - IPS Policies: Multiple, Custom
  - User-based policy creation
  - Automatic real-time updates from CRProtect networks
  - Protocol Anomaly Detection
  - DDoS attack prevention

- Web Filtering**
- Inbuilt Web Category Database
  - URL, keyword, File type block
  - Categories: Default(82+), Custom
  - Protocols supported: HTTP, HTTPS
  - Block Malware, Phishing, Pharming URLs
  - Schedule-based access control
  - Custom block messages per category
  - Block Java Applets, Cookies, Active X
  - CIPA Compliant
  - Data leakage control via HTTP, HTTPS upload

- Application Filtering**
- Inbuilt Application Category Database
  - 11+ Application Categories: e.g. Gaming, IM, P2P, Proxy
  - Schedule-based access control
  - Block
    - P2P applications e.g. Skype
    - Anonymous proxies e.g. Ultra surf
    - "Phone home" activities
    - Keylogger
  - Layer 7 (Applications) & Layer 8 (User - Identity) Visibility

- Web Application Firewall**
- Positive Protection model
  - Unique "Intuitive Website Flow Detector" technology
  - Protection against SQL Injections, Cross-site Scripting (XSS), Session Hijacking, URL Tampering, Cookie Poisoning
  - Support for HTTP 0.9/1.0/1.1
  - Extensive Logging & Reporting

- Virtual Private Network**
- IPSec, L2TP, PPTP
  - Encryption - 3DES, DES, AES, Twofish, Blowfish, Serpent
  - Hash Algorithms - MD5, SHA-1
  - Authentication - Preshared key, Digital certificates
  - IPSec NAT Traversal
  - Dead peer detection and PFS support
  - Diffie Hellman Groups - 1,2,5,14,15,16
  - External Certificate Authority support
  - Export Road Warrior connection configuration
  - Domain name support for tunnel end points
  - VPN connection redundancy
  - Overlapping Network support
  - Hub & Spoke VPN support

- SSL VPN**
- TCP&UDP Tunneling
  - Authentication - Active Directory, LDAP, RADIUS, Cyberoam
  - Multi-layered Client Authentication - Certificate, Username/Password
  - User & Group policy enforcement
  - Network access - Split and Full tunneling
  - Browser-based (Portal) Access - Clientless access
  - Lightweight SSL VPN Tunneling Client
  - Granular access control to all the Enterprise Network resources
  - Administrative controls - Session timeout, Dead Peer Detection, Portal customization
  - TCP-based Application Access - HTTP, HTTPS, RDP, TELNET, SSH

- Instant Messaging (IM) Management**
- Yahoo and Windows Live Messenger
  - Virus Scanning for IM traffic
  - Allow/Block Login
  - Allow/Block File Transfer
  - Allow/Block Webcam
  - Allow/Block one-to-one/group chat
  - Content-based blocking
  - IM activities Log
  - Archive files transferred
  - Custom Alerts

- Wireless WAN**
- USB port 3G/4G and Wimax Support
  - Primary WAN link
  - WAN Backup link

- Bandwidth Management**
- Application and User Identity based Bandwidth Management
  - Guaranteed & Burstable bandwidth policy
  - Application & User Identity based Traffic Discovery
  - Multi WAN bandwidth reporting
  - Category-based bandwidth restriction

- User Identity and Group Based Controls**
- Access time restriction
  - Time and Data Quota restriction
  - Schedule based Committed and Burstable Bandwidth
  - Schedule based P2P and IM Controls

- Networking**
- Failover - Automated Failover/Failback, Multi-WAN failover, 3GModem failover
  - WRR based load balancing
  - Policy routing based on Application and User
  - IP Address Assignment - Static, PPPoE, L2TP, PPTP & DDNS Client, Proxy ARP, DHCP server, DHCP relay
  - Support for HTTP Proxy
  - Dynamic Routing: RIP v1& v2, OSPF, BGP, Multicast Forwarding
  - Parent Proxy support with FQDN
  - "IPv6 Ready" Gold Logo

- Administration & System Management**
- Web-based configuration wizard
  - Role-based access control
  - Firmware Upgrades via Web UI
  - Web 2.0 compliant UI (HTTPS)
  - UI Color Styler
  - Command Line Interface (Serial, SSH, Telnet)
  - SNMP (v1, v2c, v3)
  - Multi-lingual support: Chinese, Hindi, French, Korean
  - Cyberoam Central Console (Optional)
  - NTP Support

- User Authentication**
- Internal database
  - Active Directory Integration
  - Automatic Windows Single Sign On
  - External LDAP/RADIUS database integration
  - Thin Client support - Microsoft Windows Server 2003 Terminal Services and Citrix XenApp
  - RSA SecurID support
  - External Authentication - Users and Administrators
  - User/MAC Binding
  - Multiple Authentication servers

- Logging/Monitoring**
- Graphical real-time and historical monitoring
  - Email notification of reports, viruses and attacks
  - Syslog support
  - Log Viewer - IPS, Web filter, Anti Virus, Anti Spam, Authentication, System and Admin Events

- On-Appliance Cyberoam-iView Reporting**
- Integrated Web-based Reporting tool - Cyberoam-iView
  - 1000+ drilldown reports
  - 45+ Compliance Reports
  - Historical and Real-time reports
  - Multiple Dashboards
  - Username, Host, Email ID specific Monitoring Dashboard
  - Reports - Security, Spam, Virus, Traffic, Policy violations, VPN, Search Engine keywords
  - Multi-format reports - tabular, graphical
  - Exportable formats - PDF, Excel
  - Automated Report Scheduling



- IPSec VPN Client\*\***
- Inter-operability with major IPSec VPN Gateways
  - Supported platforms: Windows 2000, WinXP 32/64-bit, Windows 2003 32-bit, Windows 2008 32/64-bit, Windows Vista 32/64-bit, Windows 7 RC1 32/64-bit
  - Import Connection configuration

- Certification**
- ICSA Firewall - Corporate
  - Checkmark UTM Level 5 Certification
  - PNPC - Basic and AES interoperability
  - "IPv6 Ready" Gold Logo

**Hardware Specifications**

Memory	1GB
Compact Flash	4GB

- Compliance**
- CE
  - FCC

**Dimensions**

H x W x D (inches)	
H x W x D (cms)	1.7 x 6 x 9.1
Weight	4.4 x 15.3 x 23.2 1.5kg, 3.307 lbs

**Power**

Input Voltage	100-240 VAC
Consumption	13.2W
Total Heat Dissipation (BTU)	45

**Environmental**

Operating Temperature	
Storage Temperature	0 to 40 °C
Relative Humidity (Non condensing)	-25 to 75 °C 10 to 90%

\*Antivirus, IPS and UTM performance is measured based on HTTP traffic as per RFC 3511 guidelines. Actual performance may vary depending on the real network traffic environments.

\*\*Additional Purchase Required.

**Toll Free Numbers**

USA : +1-800-686-2360 | India : 1-800-301-00013  
APAC/MEA : +1-877-777-0368 | Europe : +44-808-120-3958