



Cyberoam NG series of Unified Threat Management appliances are the Next-Generation network security appliances that include UTM security features and performance required for future networks. The NG series for SOHO offer “the fastest UTMs made for SMBs” to small offices. The best-in-class hardware along with software to match, enables the NG series to offer unmatched throughput speeds, compared to any other UTM appliance in this market segment. This assures support for future IT trends in organizations like high-speed Internet and rising number of devices in organizations – offering future-ready security for small office networks.

With Cyberoam NG series, businesses get assured Security, Connectivity and Productivity. The Layer 8 Technology treats User-Identity as the 8th Layer or the HUMAN layer in the protocol stack. It attaches User-Identity to security, which adds speed to an organization’s security by offering instant visibility into the source of attacks by username rather than only IP address. Cyberoam’s Extensible Security Architecture (ESA) supports feature enhancements that can be developed rapidly and deployed with minimum efforts, offering future-ready security to organizations.

**The ‘Next-Generation’ Series for SOHO:**  
Offering “the fastest UTMs made for SMBs” to Small Offices

Cyberoam’s **Layer 8 Technology** treats “User Identity” as the 8th Layer in the protocol stack



L8	USER	
L7	Application	
L6	Presentation	ASCII, EBCDIC, ICA
L5	Session	L2TP, PPTP
L4	Transport	TCP, UDP
L3	Network	192.168.1.1
L2	Data Link	00-17-BB-8C-E3-E7
L1	Physical	

Cyberoam UTM offers security across Layer 2-Layer 8 using Identity-based policies

**Cyberoam UTM features assure Security, Connectivity, Productivity**

**Security**

**Network Security**

- Firewall
- Intrusion Prevention System
- Web Application Firewall

**Content Security**

- Anti-Virus/Anti-Spyware
- Anti-Spam (Inbound/Outbound)<sup>##</sup>
- HTTPS/SSL Content Security

**Administrative Security**

- Next-Gen UI
- iView- Logging & Reporting



**Connectivity**

**Business Continuity**

- Multiple Link Management
- High Availability

**Network Availability**

- VPN
- 3G/4G/WiMAX Connectivity

**Future-ready Connectivity**

- “IPv6 Ready” Gold Logo



**Productivity**

**Employee Productivity**

- Content Filtering
- Instant Messaging Archiving & Controls

**IT Resource Optimization**

- Bandwidth Management
- Traffic Discovery
- Application Visibility & Control

**Administrator Productivity**

- Next-Gen UI



# Specification

## Interfaces

Copper GbE Ports	6
Configurable Internal/DMZ/WAN Ports	Yes
Console Ports (RJ45)	1
USB Ports	2

## System Performance\*

Firewall Throughput (UDP) (Mbps)	2,300
Firewall Throughput (TCP) (Mbps)	2,000
New sessions/second	12,000
Concurrent sessions	350,000
IPSec VPN Throughput (Mbps)	250
No. of IPSec Tunnels	150
SSL VPN Throughput (Mbps)	100
WAF Protected Throughput (Mbps)	65
Anti-Virus Throughput (Mbps)	525
IPS Throughput (Mbps)	350
UTM Throughput (Mbps)	210

## Stateful Inspection Firewall

- Layer 8 (User - Identity) Firewall
- Multiple Security Zones
- Access Control Criteria (ACC) - User - Identity, Source & Destination Zone, MAC and IP address, Service
- UTM policies - IPS, Web Filtering, Application Filtering, Anti-Virus, Anti-Spam and Bandwidth Management
- Layer 7 (Application) Control & Visibility
- Access Scheduling
- Policy based Source & Destination NAT
- H.323, SIP NAT Traversal
- 802.1q VLAN Support
- DoS & DDoS Attack prevention
- MAC & IP-MAC filtering and Spoof prevention

## Gateway Anti-Virus & Anti-Spyware

- Virus, Worm, Trojan: Detection & Removal
- Spyware, Malware, Phishing protection
- Automatic virus signature database update
- Scans HTTP, HTTPS, FTP, SMTP, POP3, IMAP, IM, VPN Tunnels
- Customize individual user scanning
- Self Service Quarantine area
- Scan and deliver by file size
- Block by file types
- Add disclaimer/signature

## Gateway Anti-Spam

- Inbound/Outbound Scanning
- Real-time Blacklist (RBL), MIME header check
- Filter based on message header, size, sender, recipient
- Subject line tagging
- IP address Black list/White list
- Redirect Spam mails to dedicated email address
- Image-based Spam filtering using RPD Technology
- Zero hour Virus Outbreak Protection
- Self Service Quarantine area
- Spam Notification through Digest
- IP Reputation-based Spam filtering

## Intrusion Prevention System

- Signatures: Default (4500+), Custom
- IPS Policies: Multiple, Custom
- User-based policy creation
- Automatic real-time updates from CRProtect networks
- Protocol Anomaly Detection
- DDoS attack prevention

## Web Filtering

- Inbuilt Web Category Database
- URL, keyword, File type block
- Categories: Default(82+), Custom
- Protocols supported: HTTP, HTTPS
- Block Malware, Phishing, Pharming URLs
- Schedule-based access control
- Custom block messages per category
- Block Java Applets, Cookies, Active X
- CIPA Compliant
- Data leakage control via HTTP, HTTPS upload

## Application Filtering

- Inbuilt Application Category Database
- 11+ Application Categories: e.g. Gaming, IM, P2P, Proxy
- Schedule-based access control
- Block
  - P2P applications e.g. Skype
  - Anonymous proxies e.g. Ultra surf
  - "Phone home" activities
  - Keylogger
- Layer 7 (Applications) & Layer 8 (User - Identity) Visibility

## Web Application Firewall

- Positive Protection model
- Unique "Intuitive Website Flow Detector" technology
- Protection against SQL Injections, Cross-site Scripting (XSS), Session Hijacking, URL Tampering, Cookie Poisoning
- Support for HTTP 0.9/1.0/1.1
- Extensive Logging & Reporting

## Virtual Private Network

- IPSec, L2TP, PPTP
- Encryption - 3DES, DES, AES, Twofish, Blowfish, Serpent
- Hash Algorithms - MD5, SHA-1
- Authentication - Preshared key, Digital certificates
- IPSec NAT Traversal
- Dead peer detection and PFS support
- Diffie Hellman Groups - 1,2,5,14,15,16
- External Certificate Authority support
- Export Road Warrior connection configuration
- Domain name support for tunnel end points
- VPN connection redundancy
- Overlapping Network support
- Hub & Spoke VPN support

## SSL VPN

- TCP & UDP Tunneling
- Authentication - Active Directory, LDAP, RADIUS, Cyberoam
- Multi-layered Client Authentication - Certificate, Username/Password
- User & Group policy enforcement
- Network access - Split and Full tunneling
- Browser-based (Portal) Access - Clientless access
- Lightweight SSL VPN Tunneling Client
- Granular access control to all the Enterprise Network resources
- Administrative controls - Session timeout, Dead Peer Detection, Portal customization
- TCP - based Application Access - HTTP, HTTPS, RDP, TELNET, SSH

## Instant Messaging (IM) Management

- Yahoo and Windows Live Messenger
- Virus Scanning for IM traffic
- Allow/Block Login
- Allow/Block File Transfer
- Allow/Block Webcam
- Allow/Block one-to-one/group chat
- Content-based blocking
- IM activities Log
- Archive files transferred
- Custom Alerts

## Wireless WAN

- USB port 3G/4G and Wimax Support
- Primary WAN link
- WAN Backup link

## Bandwidth Management

- Application and User Identity based Bandwidth Management
- Guaranteed & Burstable bandwidth policy
- Application & User Identity based Traffic Discovery
- Multi WAN bandwidth reporting
- Category-based bandwidth restriction

## User Identity and Group Based Controls

- Access time restriction
- Time and Data Quota restriction
- Schedule based Committed and Burstable Bandwidth
- Schedule based P2P and IM Controls

## Networking

- Failover - Automated Failover/Failback, Multi-WAN failover, 3GModem failover
- WRR based load balancing
- Policy routing based on Application and User
- IP Address Assignment - Static, PPPoE, L2TP, PPTP & DDNS Client, Proxy ARP, DHCP server, DHCP relay
- Support for HTTP Proxy
- Dynamic Routing: RIP v1& v2, OSPF, BGP, Multicast Forwarding
- Parent Proxy support with FQDN
- "IPV6 Ready" Gold Logo

## High Availability

- Active-Active
- Active-Passive with State Synchronization
- Stateful failover
- Alerts on appliance status change

## Administration & System Management

- Web-based configuration wizard
- Role-based access control
- Firmware Upgrades via Web UI
- Web 2.0 compliant UI (HTTPS)
- UI Color Styler
- Command Line Interface (Serial, SSH, Telnet)
- SNMP (v1, v2c, v3)
- Multi-lingual support: Chinese, Hindi, French, Korean
- Cyberoam Central Console (Optional)
- Network Time Protocol Support

## User Authentication

- Internal database
- Active Directory Integration
- Automatic Windows Single Sign On
- External LDAP/RADIUS database integration
- Thin Client support - Microsoft Windows Server 2003 Terminal Services and Citrix XenApp - Novell eDirectory
- RSA SecurID support
- External Authentication - Users and Administrators
- User/MAC Binding
- Multiple Authentication servers

## Logging/Monitoring

- Graphical real-time and historical monitoring
- Email notification of reports, gateway status, viruses and attacks
- Syslog support
- Log Viewer - Firewall, IPS, Web filter, Anti Virus, Anti Spam, Authentication, System and Admin Events

## On-Appliance Cyberoam-iView Reporting



- Integrated Web-based Reporting tool - Cyberoam-iView
- 1000+ drilldown reports
- 45+ Compliance Reports
- Historical and Real-time reports
- Multiple Dashboards
- Username, Host, Email ID specific Monitoring Dashboard
- Reports - Security, Virus, Spam, Traffic, Policy violations, VPN, Search Engine keywords
- Multi-format reports - tabular, graphical
- Exportable formats - PDF, Excel
- Automated Report Scheduling

## IPSec VPN Client\*\*

- Inter-operability with major IPSec VPN Gateways
- Supported platforms: Windows 2000, WinXP 32/64-bit, Windows 2003 32-bit, Windows 2008 32/64-bit, Windows Vista 32/64-bit, Windows 7 RC1 32/64-bit
- Import Connection configuration

## Certification

- ICSA Firewall - Corporate
- Checkmark UTM Level 5 Certification
- VPNC - Basic and AES interoperability
- "IPV6 Ready" Gold Logo

## Hardware Specifications

Memory	1GB
Compact Flash	2GB
HDD	250GB or higher

## Compliance

- CE
- FCC

## Dimensions

H x W x D (inches)	1.7 x 6 x 9.1
H x W x D (cms)	4.4 x 15.3 x 23.2
Weight	2.3 kg, 5.07 lbs

## Power

Input Voltage	100-240 VAC
Consumption	47.8W
Total Heat Dissipation (BTU)	163

## Environmental

Operating Temperature	0 to 40 °C
Storage Temperature	-25 to 75 °C
Relative Humidity (Non condensing)	10 to 90%

\*Antivirus, IPS and UTM performance is measured based on HTTP traffic as per RFC 3511 guidelines. Actual performance may vary depending on the real network traffic environments.

\*\*Additional Purchase Required. \*\*\*Inbound and Outbound Spam filtering cannot be used simultaneously.

## Toll Free Numbers

USA : +1-800-686-2360 | India : 1-800-301-00013  
APAC/MEA : +1-877-777-0368 | Europe : +44-808-120-3958

Copyright © 1999-2012 Cyberoam Technologies Pvt. Ltd. All Rights Reserved.  
Cyberoam and Cyberoam logo are registered trademarks of Elitecore Technologies Pvt. Ltd. Although Elitecore has attempted to provide accurate information, Elitecore assumes no responsibility for accuracy or completeness of information neither is this a legally binding representation. Elitecore has the right to change, modify, transfer or otherwise revise the publication without notice. PL-10-100252-100718

